



SINGLE-PHASE HYBRID INVERTER



DATASHEET

SUNSYNK-8K-SG01LP1

www.sunsynk.com
sales@sunsynk.com
customerservices@sunsynk.com

Model	SUNSYNK-8K-SG01LP1
Battery Input Data	
Battery Type	Lead-acid or Li-Ion
Battery Voltage Range	48Vd.c (40Vd.c ~ 60Vd.c)
Max. Charging/Discharging Current	190Ad.c (max.)
Charging Curve	3 Stages / Equalization
External Temperature Sensor	Yes
Charging Strategy for Li-Ion Battery	Self-adaption to BMS
PV String Input Data	
Max. DC Input Power	10400W
PV Input Voltage	370V (125V~500V)
MPPT Range	150~425V
Full Load DC Voltage Range	200-425V
Start-up Voltage	125V
PV Input Current	26Ad.c + 26Ad.c
Max PV Isc	44Ad.c + 44Ad.c
No. of MPPT Trackers	2
No. of Strings Per MPPT Tracker	2+2
AC Output Data	
AC Output Rated Current	8000W
Max. AC Output Power	8000W
Peak Power(off grid)	2 times of rated power, 10s
AC Output Rated Current	34.8A
Max. AC Current	34.8A
Max. Continuous AC Passthrough	50A
Power Factor	0.8 leading to 0.8 lagging
Output Frequency and Voltage	50 Hz; 230/240V 0.85Un-1.1Un
Grid Type	Single Phase
Total Harmonic Distortion (THD)	<3% (of nominal power)
DC current injection	<0.5% In
Efficiency	
Max. Efficiency	97.60%
Euro Efficiency	96.50%
MPPT Efficiency	>99%
Protection	
Integrated	PV Arc Fault Detection, PV Input Lightning Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection
Anti-islanding Protection	Integrated (Active Frequency Shift)
Surge Protection	DC Type II / AC Type II
Over Voltage Category	DC Type II / AC Type III
Certifications and Standards	
Grid Regulation	AS/NZS 4777.2
EMC/Safety Regulation	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2

General Data

Operating Temperature Range	-40~60 °C, >45 °C Derating
Cooling	Smart cooling
Noise	<30 dB
Communication with BMS	RS485; CAN
Weight	25.5kg
Cabinet size	420W×670H×233D (Excluding connectors and brackets)
Protection Degree	IP65
Installation Style	Wall-mounted
Warranty	5 years

Importer

Sunsynk Australia Pty Ltd
230 Morrison Road, Midvale, WA 6056, Australia
+618 9274 4883
Website: www.sunsynk.com.au
Email: admin@sunsynk.com.au

Manufacturer

Sunsynk Limited HK (Part of Global Tech)
7/F. Texwood Plaza, 6 How Ming Street
Kwun Tong
Kowloon
Tel: +852 2884 4318 Fax: +852 2884 4816
Website: <http://www.sunsynk.com>
E-mail: support@sunsynk.com



CONTACT US

- Call us:** +44 151 832 4300 **Email us:** sales@sunsynk.com
- HK Address:** Room 702-704, 7/F Texwood Plaza, 6 How Ming Street, Kwun Tong, Kowloon, Hong Kong.
- UK Address:** Sunsynk, 17 Turnstone Business Park, Mulberry Avenue, Widnes, Cheshire, WA8 0WN.
- SA Address:** Globaltech Sunsynk South Africa (Pty) Ltd, Unit 2 Highview Boulevard, Ferndale 2194.
- NL Address:** Sunsynk EU, Henri Wijnmalenweg 8, 5657 EP Eindhoven, Netherlands.

GlobalTech Ltd



SGS

UK
CA CE

Powered by
SUN SYNK